



FIBER FILM BETA-L

MINIMISE YOUR COST
PER PALLET



FIBER FILM BETA-L

**Up to 160%
pre-stretch**

Product Overview

Fiber Film is a novel, high efficiency stretch film with reinforcement elements (fibers) that increase tear resistance.

Fiber Film **Beta-L** operates with **Fully Automatic Wrapping Machines** that incorporate a pre-stretch unit and **performs up to 160% stretching**.


Fiber Film **Beta-L** is designed for **Light** applications and usually **replaces a stretch film of 17µm thickness or less**.

Beta-L provides:

- ✓ **Worry free performance: Place it – Forget it!**
- ✓ **No breakages during palletization**
- ✓ **Exceptional load retention & stability**

Fiber Film Beta-L

Performance Chart



The graph above illustrates how the film performs under an increased load. Where the line ends indicates where the film breaks.

Technical Specifications

		TOLERANCE
Tensile strength at break (N/mm ²)	23,9	10%
Elongation at break (%)	303	10%
Film width (mm)	485	2%
Film Weight (gr/m)	4,5	5%
Pre-Stretch up to	160%	-

Pallet dimensions: 80cm x 120cm x 115cm

Packaging Specifications

Gross Roll Weight* (kg)	12,5
Film Length per roll** (m)	2400
Roll Diameter (O.D.)*** mm	228
Core diameter (mm)	76
Core Weight (kg)	1,7
Rolls per pallet	36
Net Pallet Weight *(kg)	450
Weight Tolerance*	±5%
Length Tolerance**	±2%
Roll Diameter Tolerance***	±2%

V. 10_2017



VENETA IMBALLAGGI
PROTEGGE I TUOI PRODOTTI